

Offering flexibility to help deliver exceptional care for range of bariatric patient needs.

From lower acuity care to the ICU, hospitals are adjusting to accommodate an increasing population of bariatric patients.

Because increased lengths of stay, injuries related to mobility issues and higher readmission rates can be costly, it's critical to have access to the right equipment to provide appropriate bariatric care for a range of conditions.^{1,2}

The Excel Care® ES Bed helps you deliver exceptional care with:

- Flexible patient support
- Simplified care
- Support patient independence

Hill-Rom can help transform bariatric care.

Excel Care® ES Bariatric Bed

Adaptable Bariatric Care

Technical Specifications		Scale System Accuracy
Bed		
Low position—sleep deck to floor	17" (43.2 cm)	Weigh in any po
High position—sleep deck to floor	29" (73.7 cm)	(except Trend/R
Maximum overall width	44"-54" (111.8-137.2 cm)	Scale weight ca
Maximum overall length	91"-100" (254 cm)	Safety Listing
Patient weight capacity	1,000 lbs (453.6 kgs)	, 3
		Safety listings
Bed Angles		Power requirem
Head section	0°-48°	Fuse
Knee section	0°-20°	Maximum curre
Max Trend/Reverse Trend	12°/10°	Fire Safety
		Meets the requi
Sleep Surface & Air Supply Uni	t	Foam mattress a
Foam	80"-88"L x 40"-50"W x 8.0"H (223.5 x 101.6-127 x 20.3 cm)	rodiii iiidiliess d
Low air loss	80"-88"L x 40"-50"W x 8.5"H	Standard Feat
	(223.5 x 101.6-127 x 21.6 cm)	
Low air loss with Turn Assist	80"-88"L x 40"-50"W x 8.5"H (223.5 x 101.6-127 x 21.6 cm)	Expandable wid Battery backup
Low air loss with CLRT	80"-88"L x 40"-50"W x 8.5"H	In-bed scale
LOW dif 1055 WILLI CENT	(223.5 x 101.6-127 x 21.6 cm)	Head and Trend
Air supply unit dimensions	12.1"H x 14.5"W x 6.0"D	nead and nend
	(30.7 x 36.8 x 15.2 cm)	Optional Feat
		Patient-helper t
Caster & Braking System		Patient pendant
Caster diameter	6" (15.2 cm)	Low air loss surf
Four-wheel braking	Yes	Low air loss surf
Brakes lock both rolling and swivelling	g Yes	2011 011 1000 0011

Scale System			
Accuracy	1% of patient weight (with sleep deck flat)		
Weigh in any position (except Trend/Rev Trend)	Yes		
Scale weight capacity	1,000 lbs (453.6 kgs)		
Safety Listing & Power Requirements			
Safety listings	UL 60601-1		
Power requirements	120v, 60 cycle AC		
Fuse	5A		
Maximum current	6A		
Fire Safety	466504622		
Meets the requirements of	16CFR1632		
Foam mattress also meets	CAL129, CAL603, NFPA101, BFDIX-11		
Standard Features			
Expandable width and length frame and surface			
Battery backup			
In-bed scale			
Head and Trend angle indicators			
Optional Features			
Patient-helper trapeze			
Patient pendant (standard on rental)			
Low air loss surface with Turn Assist			
Low air loss surface with CLRT			

Hill-Rom reserves the right to make changes without notice in design, specifications and models. The only warranty Hill-Rom makes is the express written warranty extended on the sale or rental of its products.

©2015 Hill-Rom Services, Inc. ALL RIGHTS RESERVED. 174348 rev 3 29-OCT-2015 ENG – US

For further information about this product or a service, please contact your local Hill-Rom representative or visit our webpage:

USA 800-445-3730 Canada 800-267-2337 McGinley L. Best Practices for Safe Handling of the Morbidly Obese Patient. Bariatic Nursing and Surgical Patient Care. Volume 3, Number 4, 2008.

1. Rice S. Retrofitting hospitals for obese patients. Modern Healthcare. 2014

Feb. modernhealthcare.com/article/20140208/MAGAZINE/302089980.

